

Registered Office: S-42, MIDC, Bhosari, Pune - 411 026, Maharashtra, India. PH: +91 20 2712 1610 / 2712 0681 / 2712 7822 Web: www.arofines.in | Email: sales@arofines.in

AROBOND - 555 (SIDE PASTING ADHESIVE)

TYPE : Water based Synthetic Resin Adhesive

PHYSICAL CONSTANTS

APPEARANCE : Off White Viscous adhesive

VISCOSITY 30,000 - 45,000 cps

by Brookfield Viscometer RVT spindle number 6 at 20 r.p.m, at 30°C

RECOMMENDED USE: AROBOND – **555** is a specially developed adhesive for side seam pasting of PVC / BOPP / Polyester Laminated duplex Board folding boxes. Since the product is viscous it is ideally suited for hand pasting application. If used carefully, it is suitable for automatic glue pasting machines also. Please note that the surface treatment of laminated boards should be minimum 38 dynes / cm. AROBOND-555 is also recommended for use as labeling adhesive for paper labels on PET/Glass Containers by manual application.

PRECAUTIONS Stir well before use.

Close the lid tightly after use.

PACKING : 50 Kg Carboy

20 Kg Plastic Bucket

(4 X 5 Kg Plastic Bucket) packed in corrugated Box

STORAGE Store in cool and dry place.

Away from direct sunlight.

SHELF LIFE : 6 Months from the date of manufacturing if stored

properly in original packed condition, maintained strictly

under recommended storage conditions.

TDS032 w.e.f.: November 2017

DISCLAIMER: This information contained herein is believed to be accurate & presented in good faith. We do disclaim any liability resulting from the use of the contents of this information Since we cannot control and anticipate the conditions under which this product is used, we do not guarantee that similar results will be obtained by others. Appropriate lab & field trials under intended application and service conditions must be thoroughly evaluated by the user of this product to determine its suitability for a particular application. Any further modification / addition to this product will not be liable for any claim or compensation on M/s Arofine Polymers Pvt Ltd due to any fault arising after the use of the modified product. We reserve the right to alter or change specification without prior notice.

Website: www.arofines.in | Email: sales@arofines.in

