



## **AROBOND – 80** **(Pressure Sensitive Adhesive)**

**TYPE** : Water based synthetic resin based Pressure Sensitive Adhesive.

### **PHYSICAL CONSTANTS**

**APPEARANCE** : Milky white, free flowing adhesive.

**DRY FILM** : Flexible, Clear, glossy and tacky film.

**TOXICITY** : Non Toxic

**pH** : 4.00 - 6.00

**VISCOSITY** : 8,000 - 15,000 cps  
Brookfield Viscometer RVT,  
Spindel No. 5. RPM 20 @ 30° C

**USE** : AROBOND - 80 suitable adhesive for manufacturing stickers of paper/PVC/ metalised Polyester etc.

**PACKING** : 50 Kg. Plastic Carboy.  
(20 x 1) kg in corrugated box.  
5 kgs. Plastic container.  
(4 x 5) Kgs in corrugated box.

**STORAGE** : Store in cool and dry place away from heat and sunlight.

**SHELF LIFE** : 6 Months from the date of manufacturing, if stored properly in original packing condition, maintained strictly under recommended storage conditions.

TDS 037 w.e.f.: November 2017

DISCLAIMER: This information contained herein is believed to be accurate & presented in good faith. We do disclaim any liability resulting from the use of the contents of this information Since we cannot control and anticipate the conditions under which this product is used, we do not guarantee that similar results will be obtained by others. Appropriate lab & field trials under intended application and service conditions must be thoroughly evaluated by the user of this product to determine its suitability for a particular application. Any further modification / addition to this product will not be liable for any claim or compensation on M/s Arofine Polymers Pvt Ltd due to any fault arising after the use of the modified product. We reserve the right to alter or change specification without prior notice.

**Website:** www.arofines.in | **Email:** sales@arofines.in