

Registered Office: S-42, MIDC, Bhosari, Pune - 411 026, Maharashtra, India. PH: +91 20 2712 1610 / 2712 0681 / 2712 7822 Web: www.arofines.in Email: sales@arofines.in

AROVYL 810

TYPE : Water based Synthetic Emulsion

PHYSICAL CONSTANTS

APPEARANCE : Thick milky-white emulsion

pН : 4.0 - 5.0

Viscosity 24,000 - 30,000 cps

Brookfield Viscometer RVT, Spindle No.6 at 20 r.p.m. at 30°C

RECOMMENDED USE : AROVYL 810 is specially developed

emulsion for paper to paper / paper to board pasting.

Kindly ensure that the drum / carboy stirred well before use.

PACKING : 200 Kg Plastic Drum

50 Kg Plastic Carboy

: Store in cool and dry place. Away from direct sunlight **STORAGE**

SHELF LIFE : 6 Months from the date of manufacturing if stored properly

in original packed condition, maintained strictly under

recommended storage conditions.

TDS 054 w.e.f.: November 2017

DISCLAIMER: This information contained herein is believed to be accurate & presented in good faith. We do disclaim any liability resulting from the use of the contents of this information Since we cannot control and anticipate the conditions under which this product is used, we do not guarantee that similar results will be obtained by others. Appropriate lab & field trials under intended application and service conditions must be thoroughly evaluated by the user of this product to determine its suitability for a particular application. Any further modification / addition to this product will not be liable for any claim or compensation on M/s Arofine Polymers Pvt Ltd due to any fault arising after the use of the modified product. We reserve the right to alter or change specification without prior notice.

Website: www.arofines.in | Email: sales@arofines.in

