



AROVYL 815

TYPE : Water based Synthetic adhesive

PHYSICAL CONSTANTS

APPEARANCE : White, free flowing adhesive

pH : 4.0 - 6.0

Viscosity : 4,000 – 7,000 cps
Brookfield Viscometer RVT,
Spindle No.4 at 20 r.p.m. at 30°C

RECOMMENDED USE : **AROVYL 815** is specially developed ready-to-use Emulsion for side pasting of corrugated boxes, by disc/wheel Application.

AROVYL 815 has excellent grab due to the high pulp Penetration especially recommended for steeples corrugated box manufacturing.

Kindly ensure that the drum / carboy stirred well before use.

PACKING : 50 Kg Plastic Carboy

STORAGE : Store in cool and dry place.
Away from direct sunlight

SHELF LIFE : 6 Months from the date of manufacturing, if stored properly in original packing condition, maintained strictly under recommended storage conditions

TDS 150 w.e.f.: November 2017

DISCLAIMER: This information contained herein is believed to be accurate & presented in good faith. We do disclaim any liability resulting from the use of the contents of this information Since we cannot control and anticipate the conditions under which this product is used, we do not guarantee that similar results will be obtained by others. Appropriate lab & field trials under intended application and service conditions must be thoroughly evaluated by the user of this product to determine its suitability for a particular application. Any further modification / addition to this product will not be liable for any claim or compensation on M/s Arofine Polymers Pvt Ltd due to any fault arising after the use of the modified product. We reserve the right to alter or change specification without prior notice.

Website: www.arofines.in | Email: sales@arofines.in