



### Swift<sup>®</sup> melt 1908

**Type of Adhesive** Hot melt pressure sensitive adhesive.

**Product Benefits**

- excellent performance on holographic labels
- strong adhesion on wide range of substrates, both filmic and paper based
- balanced adhesion and cohesion
- clean label conversion

**Typical Applications** Designed for Tape & Label applications.

**Suitable substrates** Suitable for backing materials as films & papers.

#### Typical Properties

Property	Value
Colour	light yellow
Softening point	approx. 98°C
Viscosity (Brookfield, at 175°C)	approx. 4 000 mPa.s
Shelf life	12 months



# H.B. Fuller



## TECHNICAL DATA SHEET

**Application Instructions** Application by slot die or roller coating. Application temperature: between 160°C and 170°C, depending on the operating conditions. Application method: can be run on all standard hot melt coating systems.

**Precautions:**

Material is applied hot-appropriate clothing and eye protection should be used.

Use adequate ventilation to remove any hot melt fumes or vapours that are generated.

Keep containers and premelters covered to avoid contamination.

**Cleaning Instructions** Please contact your local Sales Office for available cleaning solutions.

**Typical Packaging** Please contact your local Sales Office for available packaging options.

**Storage Conditions** In original sealed packaging under clean and dry conditions at room temperature. Protect from sun and temperatures above +35°C.

**Disposal Advice** Please refer to the MSDS for disposal instructions.

**Safety Advice** Please refer to the MSDS for safety advice.

**Our Focus is Clear. Perfecting Adhesives.**

**IMPORTANT:** The information, specifications, procedures and recommendations herein (together "information") are based on our experience and we believe these to be accurate. No representation, guarantee or warranty is made as to the accuracy or completeness of the information or that the information will avoid losses or damages or give desired results. It is purchaser's sole responsibility to test and determine the suitability of any product for the intended use. Tests should be repeated if materials or conditions change in any way. No employee, distributor or agent has any right to change these facts and offer a guarantee of performance.

**NOTE TO USER:** by ordering/receiving product you accept the H.B. Fuller General Terms and Conditions of Sale applicable in the region. Please request a copy if you have not received these. These Terms and Conditions contain disclaimers of implied warranties (including but not limited to disclaiming warranties of fitness for a particular purpose) and limits of liability. All other terms are rejected. In any event, the total aggregate liability of H.B. Fuller for any claim or series of related claims however arising, in contract, tort (including negligence), breach of statutory duty, misrepresentation, strict liability or otherwise, is limited to replacement of affected products or refund of the purchase price for affected products. H.B. Fuller shall not be liable for loss of profit, loss of margin, loss of contract, loss of business, loss of goodwill or any indirect or consequential losses arising out of or in connection with product supply.

Nothing in any term shall operate to exclude or limit H.B. Fuller's liability for fraud, gross negligence or for death or personal injury caused by negligence or for breach of any mandatory implied terms.



## H.B. Fuller

**H.B. Fuller Company**

info-europe@hbfuller.com  
www.hbfuller.com/  
eimea/contact-us