

Fasson® Fasset Sheet Mirror / Permanent

Product Identification Number: BM13240

Facestock:**Fasson® FasSheet Mirror Plus[®]** :A bright white mirror finished cast coated paper with superior ink receptivity.**Basis Weight:** 80 gsm \pm 10% (ISO 536)**Caliper:** 0.083mm \pm 10%(ISO 534)**Adhesive:****Fasson® Permanent:** A general purpose permanent rubber based adhesive featuring high initial tack and good bond strength.**Minimum Application Temperature:** 5° C
*(The minimum temperature at which the label can be applied and will adhere)***Service Temperature Range :** -20° C to + 70° C
*(The temperature range to which the label can be exposed after the adhesion bond to the substrate has been formed)***Liner:****Fasson® Kraft:** A super-calendered kraft liner with excellent strength properties.**Basis Weight:** 65 gsm \pm 10% (ISO 536)**Caliper:** 0.062mm \pm 10%(ISO 534)**Application and Use:**

Typical applications include labels for Cosmetics, Toiletries, other Health and Beauty Aids products, House hold Chemicals and Promotional Labeling. Fasson® adhesive is in compliance with FDA 175.105 recommendations.

Conversion:**Fasson® FasSheet MirrorPlus** product is engineered to provide good performance in sheet fed converting process. The product is suited to single and/or multicolour line printing by Offset. **Exposure of sheets to high humidity conditions should be minimized.****Shelf Life :**

Two years when stored at 22° C / 50% RH.

As with all self-adhesive materials, this product should be tested thoroughly under end-use conditions to make sure it meets the requirements of the specific application.

Version 35100014

Avery Dennison (India) Pvt. Ltd.
 Narsinghpur Industrial Area
 Six Kilometer stone
 Delhi-Jaipur Highway
 Gurgaon-122001, Haryana
 Tel +91-124—2215581/582/583
 Fax +91-124-2215591/592

