



## **TECHNICAL DATA SHEET**

## **HL 55**

Type of Adhesive Protein adhesive

**Product Benefits** > Fast, aggressive initial tack with a fast speed of set

Excellent mileage

Clean machining

> Excellent non-warp quality and good film flexibility

Excellent adhesion on most substrates

Typical Applications HL 55 is a premium quality cake type Glue made from

Technical Protein and suitable for hard case making

Suitable substrates Paper, board and other substrates

## **Typical Properties**

Property	Value
Colour	Amber
Viscosity ( Brookfield RV Type, cps)	1600 cps ± 150 cps @ 0% dilution @ 65°C
% Solid Content	50 – 56%
Clean up & recommended dilution	Hot water and 0% to 10% by weight
Shelf life	Use product within 60 days. For best results and longest storage – life, store product below 32°C and avoid excessive heat for extended periods of time.

Last Updated: 11/01/2016





TECHNICAL DATA SHEET

Application

Apply with roller system

Instructions

Recommended application temperature : 60 - 65 deg.C It is important to ensure that the desired level of adhesion is obtained on necessary substrates including long term tests

**Cleaning Instructions** 

Cleaning with hot water.

Please contact your local sales office for available products.

**Typical Packaging** 

Please contact your local Sales Office for available packaging

options.

**Storage Conditions** 

In original sealed packaging at ambient temperature. Store in a

cool, dry place always & away from direct sunlight.

**Disposal Advice** 

Please refer to the MSDS for disposal instructions.

Safety Advice

Please refer to the MSDS for safety advice.

Last Updated: 11/01/2016