

Facestock

A coated, Matte white wood free paper with black back designed for cover up application

Basis Weight

Caliper

 $75 \text{ gsm} \pm 5 \text{ gsm}$ $62 \mu m \pm 5 \mu m$

ISO 536 ISO 534

Adhesive

A permanent rubber based adhesive featuring ultra high initial tack and ultimate bond strength.

Liner

A clay coated kraft liner featuring excellent strength characteristics.

Basis Weight

 $100 \text{ gsm} \pm 6 \text{ gsm}$

ISO 536

Caliper

100 μ m ± 6 μ m

ISO 534

Laminate

Total Caliper

 $180 \, \mu m \pm 10 \, \mu m$

Typical Performance Data

Initial Tack Peel Adhes, 90°

14 8.5 N/25 mm

FTM 9 glass.

Min. appl. temp.

0°C

N/25 mm

FTM 2 st.st.

Service temp.

-20°C to 80°C subject to facestock limitations

*Typical Performance Data only serves as reference to product performance under specified testing conditions and does not represent a product specification. Customers are recommended to test under actual conditions of use to determine its suitability.

Applications and Use

Typical applications include labels for overlabelling where high opacity is needed to cover previous information. The product is also suitable, where excellent barrier properties of label are desired.

Food Industry Labels: The adhesive used in this product is in compliance with FDA 175.105 recommendations.

Conversion/Printing


Fasson® Black Back product is engineered for optimum performance in roll fed applications. The product is suited to single and/or multicolour line printing by Flexo, Offset and Letterpress.

Shelf life

To obtain optimal performance, use this product within one year of the date of manufacture, under storage conditions as defined by FINAT (20- 25°C; 40-50%RH). Storage at higher temperatures and/or humidity levels for extended periods of time can reduce shelf life.

SW8659

Fasson Matt Black Back Paper/S2060/CCK100W HIMP



Matt Black Back



CCK100 WH IMP

FDA.175.105

ROHS

Avery Dennison India Pvt. Ltd.

Gurgaon:

Narsinghpur Industrial Area, Delhi - Jaipur Highway, District Gurgaon, Haryana. India. 122001 Tel: +91 124 4351200

G-5 MIDC Ranjangaon Industrial Area, Taluka - Shirur District - Pune, Maharashtra India, 412220 Tel: +91 2138 664200

Bengaluru:

Plot No. 18 & 23, Peenya Industrial Area, Phase-I, Yeshwantpur Hobli, District - Bengaluru, Karnataka India, 560058 Tel: +91 80 43316888

All statements, technical information and recommendations about AVERY DENNISON products are based upon tests believed to be reliable but do no consulute a guarantee or warranty. All AVERY DENNISON products are sold with the understanding that PURCHASER has products on warranted to be true of defects in material or workmanship for a period of one year from the date of shipment. Any product shown to the satisfaction of AVERY DENNISON within the unic provided to be so defective shall be replaced without charge and AVERY DENNISON within the satisfaction of AVERY DENNISON within the unic provided to be so defective shall be replaced without charge and AVERY DENNISON. independently determined the suitability of such products for it purposes. APERY DENNISON issue credit in such case as it seem reasonable however, in no event shall AVERY DENNISON be responsible for claims beyond the replacement value of the defective product or in any way

liable or responsible for consequential or incidental damages. NO EXPRESS WARRANTIES, WHETHER OF MERCHANTABILITY OR FITNESS FOR ANY ARTICULAR USE, OR OTHERWISE, EXCEPT AS SET FORTH ABOVE (WHICH IS MADE EXPRESSLY IN LIEU OF ALL OTHER WARRANTIES) SHALL APPLY TO PRODUCTS SOLD BY AVERY DENNISON. AVERY DENNISON

DENNISON. No salesman, representative, or agent of AVERY DENNISON is authorized to give any guarantee, warranty or make any representation contrary to the above.