

Facestock

A thermal transfer printable white matte ultradelaminable film.

Basis Weight: 60 gsm ± 10% ISO 536
Caliper: 90 µm ± 10% ISO 534

Adhesive

An aggressive, permanent rubber based adhesive featuring good initial tack and ultimate adhesion.

Liner

A clay coated kraft liner featuring excellent strength characteristics.

Basis Weight: 100 gsm ± 10% ISO 536
Caliper: 100 µm ± 10% ISO 534

Laminate

Total Construction Caliper 200 µm ± 10%

Performance data

Initial Tack 650 N/m FTM 9 glass
Peel Adhes.90° 350 N/m FTM 2 st. st.
Min. Appl. Temp. 5°C
Service Temp. -20°C to 70°C

Applications and use


This film is ultradestructable by delamination. This fragility associated with the high adhesive performance allows tamper evidence characteristics to these labels. Preliminary testing on the substrate is necessary to confirm the right working of label.

Conversion/printing

Fasson® TTE can be printed by all conventional printing technologies including offset, letterpress, UV-screen and thermal transfer. Compatible with wide range of wax, wax-resin and resin thermal transfer ribbons, however testing of ribbon is recommended for compatibility.

Shelf life

One year when stored at 22°C at 50% RH.

TR-1523
Fasson 90u TTE
Sheet/S2060/CCK100WH IMP

TTE
S2060
CK100Wh IMP

Avery Dennison India Pvt. Ltd.

Gurgaon :

Narsinghpur Industrial Area,
Delhi – Jaipur Highway,
District Gurgaon, Haryana,
India. 122001

Tel: +91 124 4351200

Pune :

G-5, MIDC Ranjangaon Industrial Area,
Taluka - Shirur,
District – Pune, Maharashtra
India. 412220

Tel: +91 2138 664200

Bengaluru :

Plot No. 18 & 23, Peenya Industrial Area,
Phase-I, Yeshwantpur Hobli,
District – Bengaluru, Karnataka
India. 560058

Tel: +91 80 43316888

Warranty

All statements, technical information and recommendations about AVERY DENNISON products are based upon tests believed to be reliable but do not constitute a guarantee or warranty. All AVERY DENNISON products are sold with the understanding that PURCHASER has independently determined the suitability of such products for its purposes. AVERY DENNISON products are warranted to be free of defects in material or workmanship for a period of one year from the date of shipment. Any product shown to the satisfaction of AVERY DENNISON within the time provided to be so defective shall be replaced without charge of AVERY DENNISON may issue credit in such amount as it seems reasonable however, in no event shall AVERY DENNISON be responsible for claims beyond the replacement value of the defective product or in any way

liable or responsible for consequential or incidental damages. NO EXPRESS WARRANTIES, WHETHER OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR USE, OR OTHERWISE, EXCEPT AS SET FORTH ABOVE (WHICH IS MADE EXPRESSLY IN LIEU OF ALL OTHER WARRANTIES) SHALL APPLY TO PRODUCTS SOLD BY AVERY DENNISON. AVERY DENNISON SPECIFICALLY DISCLAIMS AND EXCLUDES ALL OTHER SUCH WARRANTIES. NO WAIVER, ALTERNATION, ADDITION OR MODIFICATION OF THE FOREGOING CONDITIONS SHALL BE VALID UNLESS MADE IN WRITING AND SIGNED BY AN EXECUTIVE OFFICER OF AVERY DENNISON. No salesman, representative, or agent of AVERY DENNISON is authorized to give any guarantee, warranty or make any representation contrary to the above.